

AK-C7412 MEDICAL KEYBOARD COMPACT TP



Disinfectable Medical Keyboard with numpad and touchpad

- Fully sealed with IP68 rating
- CleanFunction enables the keys to be switched off during cleaning
- Smooth, comfortable tactile typing experience



Product images may vary depending on the country layout

This innovative AK-C7412 Medical Keyboard combines a full number pad and an integrated touchpad, offering unparalleled versatility in any clinical or industrial setting. Its sleek, ergonomic design and the integrated scissor technology ensure a perfect typing feel, allowing for smooth and responsive input, even during long shifts. But what truly sets this keyboard apart is its exceptional disinfection capabilities due to the flat key profile. The durable silicone cover can withstand rigorous cleaning protocols, ensuring a safe and hygienic workspace. With the touchpad, you can easily navigate without the need for an external mouse, maximizing your efficiency and minimizing clutter.

FUNCTION AND PERFORMANCE

- Compact Medical keyboard for applications where hygiene is crucial
- Ultra-flat key profile ensures maximum wipe disinfection while maintaining optimal haptics for an excellent typing experience
- Approved for wipe disinfection according to CDC Guideline for Disinfection and Sterilization in Healthcare Facilities with EPA-registered disinfecting products

TECHNICAL DATA

| | |
|--|---|
| Weight main product: | 21 oz |
| Weight of product without packaging: | 21.16 oz |
| Dimensions product without packaging: | 14,37 in x 5,47 in x 0,67 in |
| Weight of product incl. packaging: | 25.4 oz |
| Dimensions product incl. packaging: | 15,35 in x 7,09 in x 0,98 in |
| Content of master carton (pieces): | 20 |
| Weight of master carton incl. content: | 469.14 oz |
| Dimensions master carton: | 15.75 in x 10.75 in x 17.6 in |
| Cable-length: | 5.91 ft |
| Storage temperature: | -4 °F - 140 °F |
| Working temperature: | 32 °F - 122 °F |
| Product approvals: | <ul style="list-style-type: none">• CE• EU RoHS• FCC• EN60601-1-2-2015 (IEC 4th edition) |
| System Requirements-Hardware: | USB-A |
| Operating system: | All operating systems that support USB keyboard interface |
| Scope of delivery: | <ul style="list-style-type: none">• Keyboard• Manual |
| Switching characteristics: | tactile |
| Max. current consumption (mA) of keyboard: | 32 mA |
| Actuating force (cN): | 60 cN |
| Total Key Travel: | 2,5 mm |

Key labeling: Silk screen printing on silicon membrane

Number of keys: 105

Special key functions:

- FN Key
- CleanFunction

Status LEDs: in housing

Key technology: Scissor

Keycap material: ABS

Protection class: IP 68

Warranty: 2 years warranty

Errors, technical changes and delivery options reserved. Technical information refers only to the specification of the products. Properties are not guaranteed.

| SKU / EAN / UPC | Protection class | Color | Layout |
|---|------------------|-------|---------------------|
| AK-C7412F-GUS-B/US EAN 7061112707693 UPC | IP 68 | black | US (USA) |
| AK-C7412F-GUS-W/FR EAN 7061119932685 UPC | IP 68 | white | FR (France) |
| AK-C7412F-GUS-W/GE EAN 7061117428074 UPC | IP 68 | white | DE (Germany) |
| AK-C7412F-GUS-W/NOR EAN 7061119200609 UPC | IP 68 | white | PN (PanNordic) |
| AK-C7412F-GUS-W/UK EAN 4025112099519 UPC | IP 68 | white | GB (United Kingdom) |

Please contact your local CHERRY service and support teams or your CHERRY sales partners for versions available in your country.